

Transporter Li-ion Scale

1500 kg



- ✓ lift
- ✓ weigh
- ✓ transport



optional



2nd battery extends working time between charges



support castors for wider or heavier loads

- ✓ kg or lb
- ✓ tare
- ✓ totalisation
- ✓ auto switch-off



simple, user friendly controls



creep (turtle) speed

Compact powered truck with weighing scale

Fully powered for near effortless pallet handling and check weighing

High quality Ravas scale with 4 load cells, gives high weighing accuracy of 0.1% in 1kg increments

Weighs in kg or lb, tare & totalisation functions, auto switch-off

Pull out lithium-ion battery with estimated working time of 5 hours between charges

Optional second battery: increases working time to estimated 11 hours, for heavier use

Optional support castors: recommended when handling wider and/or heavier loads

Width of only 590mm and creep (turtle) speed, allows trucks to be used in very confined spaces

1 year parts & labour warranty

Transporter Li-ion Scale

Specification



Lift & Weigh Capacity	kg	1500
Service Weight	kg	155
Battery Weight	kg	5
Fork Height, lowered	mm	90
Fork Height, raised	mm	185
Fork Dimensions (H x W x L)	mm	60 x 155 x 1150
Distance Between Fork Arms	mm	560
Load Centre Distance	mm	600
Overall Length	mm	1575
Overall Width	mm	590
Scale Indicator Model		Ravas 1100
Scale Indicator Battery Voltage	V/Ah	4 x 1.5
No of Load Cells		4
Weighing Accuracy	%	0.1 of applied load
Weighing Increments	kg	1
Display Digits		5
Digit Height	mm	18
Travel speed, laden/unladen	km/h	4/4.5
Lifting Speed, laden/unladen	m/s	0.017/0.023
Gradeability, laden/unladen	%	5/16
Battery Voltage/Rated Capacity (5h)	v/Ah	24/20
Charger	v/Ah	External 24/4
Drive Motor Rating (S2 60 min)	kW	0.75
Lift Motor Rating (S3 15%)	kW	0.5
Ground Clearance, centre of wheelbase	mm	25
Service Brake Type		Electromagnetic
Type of Drive Control		DC
Tyre Type driving wheels/loading wheels		PU/PU
Sound Level at Driver's Ear	dB (A)	<74

Units 10 & 11 Bridgwater Court, Oldmixon Crescent, Weston-super-Mare BS24 9AY

Tel: +44 (0)1934 621777 Email: sales@howardhandling.co.uk Web: howardhandling.co.uk